

# BURNISHING

## Tools Needed

- 1500+ RPM Floor Machine (Battery, Propane or Cord Electric)
- Floor Pads



## Product Needed

Optional  
P&G Pro Line  
Spray Buff / Maintainer




**FREQUENCY:** Daily or as needed to repair surface imperfections that cannot be repaired with daily maintenance procedures.

**PREPARATION:** Collect all tools, equipment and products required. Ensure all equipment is operational. Choose appropriate safety equipment.

**SPECIAL DIRECTIONS FOR THIS TASK:** Floor must be completely dry before burnishing. When finished, clean and return equipment to storage area.

**NOTE:** Spray Buff / Maintainer may be used as a burnishing aid. Follow the Mop-on Restorer procedure for using Spray Buff / Maintainer as a burnishing aid.



### STEP 1

- Remove grit and loose soil by following the Dust Mop Procedure.



### STEP 2


- Wet clean floor using one of the following procedures: Damp Mop Procedure, Disinfecting Damp Mop Procedure or Automatic Scrubber Floor Cleaning Procedure.



### STEP 3


- Post "out of service" sign in area to be serviced.

**NOTE:** Floors must be completely dry before burnishing.



### STEP 4

- Mount appropriate floor pad to machine.



### STEP 5

- Starting along baseboard at farthest point from door, push machine forward. Move in a straight line.
- Pivot machine at turning point, slightly overlapping last pass.

**NOTE:** Keep floor machine moving while buffing. Running machine in same spot can leave deep swirls in the finish.

**NOTE:** Flip or change floor pads frequently.



### STEP 5

- Dust mop area to remove dust resulting from burnishing operation following the Dust Mop Procedure.